



DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION

FOR CERTIFICATE NO. CL15020251

Certificate Issued To: HESSE GMBH & CO. KG

Warendorfer Strabe 21, 59075 Hamm, Germany.

Applicable Standard Specification: 2017 Al Sa'fat - Dubai Green Building Evaluation System.

Applicable Specific Rules: DM-DCLD-RD-DP21-2180-(IC) Specific Rules for Certification

of Paints and Coating through Factory Assessment as per the

2017 Al Sa'fat - Dubai Green Building Evaluation System.

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
1	Water base – One pack performance coating Coatings (other than paint). (For Interior Applications)	Hesse Hydro Isolating-Filler (HP 6645-9343)	VOC (Al Sa'fat-DGBES limit is Max. = 140 g/l)
		Hesse HYDRO TOP SEIGEL, Semi Mat	
		Hesse HYDRO Isolating filler (HP 6633-9343)	
		Hesse HYDRO Metallic lacquer (HB 65445-RAL 9006)	
	Solvent base - One pack performance coating. Coatings (other than paint). (For Interior Applications)	Hesse UV Multicoat Lacquer for Spraying (YUE 76059)	
		Hesse UV Spray Primer (YUG 7654)	VOC (Al Sa'fat-DGBES limit is Max. = 500 g/l);
2		Hesse UV Spray Primer (YUG 7600)	
		Hesse UV Colour Primer for Spraying (YUP 7600- 9343)	
		Hesse UV Top Coat for Spraying (YUU 76206)	
	Water base - Two pack reactive performance coating for specific end use such as floors Coatings (other than paint). (For Interior Applications)	Hesse HYDRO-PUR TOPCOAT	
		(HDE 5430x)	-
		Hesse HYDRO-PU Glass colour lacquer	
		(HDB 57485-RAL 9010)	VOC (Al Sa'fat-DGBES limit is Max. = 140 g/l);
3		Hesse HYDRO Crosslinker (HDR 5002)	
		Hesse PURA-ONE (HDE 51-4); Hesse HYDRO Hardener (HDR 71)	3/
		Hesse HYDRO-PU PRIMO (HDE 5400X)	
		Hesse HYDRO-PU Brillant primer (HDG 5407); Hesse HYDRO Hardener (HDR 5091)	





DUBAI CENTRAL LABORATORY DEPARTMENT DCL PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION

FOR CERTIFICATE NO. CL15020251

4	Solvent base - Two pack reactive performance coating for specific end use such as floors. Coatings (other than paint) (For Interior Applications)	Hesse SUN-CAPE PU Base Coat (DG 416) Hesse PU Isolating Filler (DP 4784-9343) Hesse UV Basecoat for Roller Coating (YPUG 7541-0007) Hesse UV Colour Primer for Roller Coating (YPUP 7391-9343) Hesse UV Top Coat for Roller Coating (YPUU 74505) Hesse UV Basecoat for Roller Coating (YPUG 7202) Hesse FANTASTIC-COLOR (DB 48885-Colours); Hesse PU Hardener (DR 4075)	VOC (Al Sa'fat-DGBES limit is Max. = 550 g/l);
5	Water base – Multi colored coating. Coatings (other than paint). (For Interior Applications)	Hesse HYDRO PRO-COLOR; (HB 65285) Colour Tone	VOC (Al Sa'fat-DGBES limit is Max. = 100 g/l)

NOTE 1: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

NOTE 2: The above product shall bear the DCL Conformity Mark (applied on each product or on the packaging).

Original Issue Date: 03 August 2015
Current Issue Date: 03 August 2021
Valid Until: 02 August 2022

for /ARIF HUSAIN AL MARZOOQI

Products Conformity Assessment Section Manager

Dubai Central Laboratory Department