

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse PU Hardener DR 4040

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

|        |  |
|--------|--|
|        | REACHSET 1000  |
| SU3    | Industrial uses: Uses of substances as such or in preparations at industrial sites               |
| ERC4   | Industrial use of processing aids in processes and products, not becoming part of articles       |
| ERC5   | Industrial use resulting in inclusion into or onto a matrix                                      |
| PROC7  | Industrial spraying  |
|        | REACHSET 2001  |
| SU22   | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a  | Wide dispersive indoor use of processing aids in open systems                                    |
| ERC8c  | Wide dispersive indoor use resulting in inclusion into or onto a matrix                          |
| PROC11 | Non industrial spraying  |

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
 Warendorfer Strasse 21  
 59075 Hamm  
 Telephone no. +49 (0) 2381 963-00  
 Fax no. +49 (0) 2381 963-849  
 E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

|  |  |      |
|--|--|------|
| Classification (Regulation (EC) No. 1272/2008) |  |      |
| Flam. Liq. 2                                   |  | H225 |
| Eye Irrit. 2                                   |  | H319 |
| Resp. Sens. 1                                  |  | H334 |
| Skin Sens. 1                                   |  | H317 |
| STOT SE 3                                      |  | H336 |

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
 For explanation of abbreviations see section 16.

### 2.2. Label elements

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

## Labelling according to regulation (EC) No 1272/2008

### Hazard pictograms



### Signal word

Danger

### Hazard statements

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.  |
| H319 | Causes serious eye irritation.   |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H317 | May cause an allergic skin reaction.                                       |
| H336 | May cause drowsiness or dizziness.   |

### Precautionary statements

|                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P261           | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P284           | [In case of inadequate ventilation] wear respiratory protection.   |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P342+P311      | If experiencing respiratory symptoms: Call a POISON CENTER or doctor.  |

### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

|          |   |
|----------|---|
| contains | m-Tolylidene diisocyanate; polyisocyanate, aromatic; Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene-trimethanol; ethyl acetate |
|----------|---|

### Supplemental information

|        |   |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking.   |
| EUH204 | Contains isocyanates. May produce an allergic reaction. |

## 2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

## 3. Composition/information on ingredients

### Hazardous ingredients

#### n-butyl acetate

|  |                  |   |      |   |                |
|--|------------------|---|------|---|----------------|
| CAS No.  | 123-86-4         |   |      |   |                |
| EINECS no.                                     | 204-658-1        |   |      |   |                |
| Registration no.                               | 01-2119485493-29 |   |      |   |                |
| Concentration                                  | >= 25            | < | 50   | % |                |
| Classification (Regulation (EC) No. 1272/2008) | Flam. Liq. 3     |   | H226 |   |                |
|  | STOT SE 3        |   | H336 |   | Nervous system |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

EUH066

**polyisocyanate, aromatic**

CAS No. 528598-79-0  
 Concentration  $\geq$  25 < 50 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Eye Irrit. 2 H319  
 Skin Sens. 1 H317

**Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene-trimethanol**

CAS No. 53317-61-6  
 EINECS no. 500-120-8  
 Concentration  $\geq$  10 < 25 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Eye Irrit. 2 H319  
 Skin Sens. 1 H317

**4-methylpentan-2-one**

CAS No. 108-10-1  
 EINECS no. 203-550-1  
 Registration no. 01-2119473980-30  
 Concentration  $\geq$  10 < 20 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Flam. Liq. 2 H225  
 Acute Tox. 4 H332 Route of exposure: Inhalation exposure  
 Eye Irrit. 2 H319  
 STOT SE 3 H335 Respiratory tract  
 EUH066

**ethyl acetate**

CAS No. 141-78-6  
 EINECS no. 205-500-4  
 Registration no. 01-2119475103-46  
 Concentration  $\geq$  1 < 10 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Flam. Liq. 2 H225  
 Eye Irrit. 2 H319  
 STOT SE 3 H336 Nervous system  
 EUH066

**m-Tolylidene diisocyanate**

CAS No. 26471-62-5  
 EINECS no. 247-722-4  
 Registration no. 01-2119454791-34  
 Concentration  $\geq$  0,1 < 0,3 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Carc. 2 H351  
 Acute Tox. 2 H330  
 Eye Irrit. 2 H319  
 STOT SE 3 H335 Respiratory tract

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|                   |      |
|-------------------|------|
| Skin Irrit. 2     | H315 |
| Resp. Sens. 1     | H334 |
| Skin Sens. 1      | H317 |
| Aquatic Chronic 3 | H412 |

Concentration limits (Regulation (EC) No. 1272/2008)

Resp. Sens. 1 H334  $\geq 0,1 \%$ **Note**

For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

**4. First aid measures****4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

**After inhalation**

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

**After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

**After ingestion**

Do not induce vomiting. Take medical treatment.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitisation of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest.

**4.3. Indication of any immediate medical attention and special treatment needed****Hints for the physician / treatment**

Treat symptomatically.

**5. Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

**Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

## 5.2. Special hazards arising from the substance or mixture

Vapours can form an explosive mixture with air.

## 5.3. Advice for firefighters

### Other information

Standard procedure for chemical fires.

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this mixture is used. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

**Hints on storage assembly**

Keep away from oxidising agents, strongly alkaline and strongly acid materials, amines, alcohols and water.

**Storage classes**

Storage class according to TRGS 510      3                      Flammable liquid

**Further information on storage conditions**

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

**7.3. Specific end use(s)**

See exposure scenario, if available.

**8. Exposure controls/personal protection****8.1. Control parameters****Exposure limit values****4-methylpentan-2-one**

|                           |                       |                   |    |        |
|---------------------------|-----------------------|-------------------|----|--------|
| List                      | Directive 2017/164 EG |                   |    |        |
| Value                     | 83                    | mg/m <sup>3</sup> | 20 | ppm(V) |
| Short term exposure limit | 208                   | mg/m <sup>3</sup> | 50 | ppm(V) |
| Status:                   | 12/2009               |                   |    |        |

**4-methylpentan-2-one**

|                                    |                     |                   |     |        |
|------------------------------------|---------------------|-------------------|-----|--------|
| List                               | EH40                |                   |     |        |
| Value                              | 208                 | mg/m <sup>3</sup> | 50  | ppm(V) |
| Short term exposure limit          | 416                 | mg/m <sup>3</sup> | 100 | ppm(V) |
| Skin resorption / sensibilisation: | Sk; Status: 01/2020 |                   |     |        |

**ethyl acetate**

|                           |                       |                   |     |        |
|---------------------------|-----------------------|-------------------|-----|--------|
| List                      | Directive 2017/164 EG |                   |     |        |
| Value                     | 734                   | mg/m <sup>3</sup> | 200 | ppm(V) |
| Short term exposure limit | 1468                  | mg/m <sup>3</sup> | 400 | ppm(V) |
| Status:                   | 02/2017               |                   |     |        |

**ethyl acetate**

|                           |         |                   |     |        |
|---------------------------|---------|-------------------|-----|--------|
| List                      | EH40    |                   |     |        |
| Value                     | 734     | mg/m <sup>3</sup> | 200 | ppm(V) |
| Short term exposure limit | 1468    | mg/m <sup>3</sup> | 400 | ppm(V) |
| Status:                   | 01/2020 |                   |     |        |

**n-butyl acetate**

|                           |         |                   |     |        |
|---------------------------|---------|-------------------|-----|--------|
| List                      | EH40    |                   |     |        |
| Value                     | 724     | mg/m <sup>3</sup> | 150 | ppm(V) |
| Short term exposure limit | 966     | mg/m <sup>3</sup> | 200 | ppm(V) |
| Status:                   | 01/2020 |                   |     |        |

**n-butyl acetate**

|                           |                       |                   |     |        |
|---------------------------|-----------------------|-------------------|-----|--------|
| List                      | Directive 2017/164 EG |                   |     |        |
| Value                     | 241                   | mg/m <sup>3</sup> | 50  | ppm(V) |
| Short term exposure limit | 723                   | mg/m <sup>3</sup> | 150 | ppm(V) |
| Status:                   | 10/2019               |                   |     |        |

**Other information**

-

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

**n-butyl acetate**

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 11                             | mg/kg/d |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 600                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 600                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 300                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 300                            | mg/m <sup>3</sup> |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 6                              | mg/kg/d |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Oral exposure                  |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 2                              | mg/kg/d |

|                      |                                |  |
|----------------------|--------------------------------|--|
| Type of value        | Derived No Effect Level (DNEL) |  |
| Reference group      | Consumer                       |  |
| Duration of exposure | Short-term                     |  |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 300 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Short-term  
 Route of exposure inhalative  
 Mode of action Local effects  
 Concentration 300 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long-term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 35,7 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long-term  
 Route of exposure inhalative  
 Mode of action Local effects  
 Concentration 35,7 mg/m<sup>3</sup>

**4-methylpentan-2-one**

Type of value Derived No Effect Level (DNEL)  
 Reference group Workers (professional)  
 Duration of exposure Short-term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 208 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Workers (professional)  
 Duration of exposure Short-term  
 Route of exposure inhalative  
 Mode of action Local effects  
 Concentration 208 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Workers (professional)  
 Duration of exposure Long-term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 83 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Workers (professional)  
 Duration of exposure Long-term  
 Route of exposure inhalative  
 Mode of action Local effects  
 Concentration 83 mg/m<sup>3</sup>



Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 11,8                           | mg/kg/d |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 14,7                           | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 14,7                           | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 155,2                          | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 155,2                          | mg/m <sup>3</sup> |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 4,2                            | mg/kg/d |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Oral exposure                  |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 4,2                            | mg/kg/d |

**ethyl acetate**

|                 |                                |  |
|-----------------|--------------------------------|--|
| Type of value   | Derived No Effect Level (DNEL) |  |
| Reference group | Workers (professional)         |  |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | Dermal exposure                |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 63                             | mg/kg/d           |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 734                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 734                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 1468                           | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 1468                           | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 734                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 734                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | Dermal exposure                |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 37                             | mg/kg/d           |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|                                  |                                |                   |
|----------------------------------|--------------------------------|-------------------|
| Type of value                    | Derived No Effect Level (DNEL) |                   |
| Reference group                  | Consumer                       |                   |
| Duration of exposure             | Long-term                      |                   |
| Route of exposure                | inhalative                     |                   |
| Mode of action                   | Systemic effects               |                   |
| Concentration                    | 367                            | mg/m <sup>3</sup> |
|                                  |                                |                   |
| Type of value                    | Derived No Effect Level (DNEL) |                   |
| Reference group                  | Consumer                       |                   |
| Duration of exposure             | Long-term                      |                   |
| Route of exposure                | Oral exposure                  |                   |
| Mode of action                   | Systemic effects               |                   |
| Concentration                    | 4,5                            | mg/kg/d           |
|                                  |                                |                   |
| Type of value                    | Derived No Effect Level (DNEL) |                   |
| Reference group                  | Consumer                       |                   |
| Duration of exposure             | Long-term                      |                   |
| Route of exposure                | inhalative                     |                   |
| Mode of action                   | Local effects                  |                   |
| Concentration                    | 367                            | mg/m <sup>3</sup> |
|                                  |                                |                   |
| <b>m-Tolyldiene diisocyanate</b> |                                |                   |
| Type of value                    | Derived No Effect Level (DNEL) |                   |
| Reference group                  | Workers (professional)         |                   |
| Duration of exposure             | Short-term                     |                   |
| Route of exposure                | inhalative                     |                   |
| Mode of action                   | Systemic effects               |                   |
| Concentration                    | 0,14                           | mg/m <sup>3</sup> |
|                                  |                                |                   |
| Type of value                    | Derived No Effect Level (DNEL) |                   |
| Reference group                  | Workers (professional)         |                   |
| Duration of exposure             | Short-term                     |                   |
| Route of exposure                | inhalative                     |                   |
| Mode of action                   | Local effects                  |                   |
| Concentration                    | 0,14                           | mg/m <sup>3</sup> |
|                                  |                                |                   |
| Type of value                    | Derived No Effect Level (DNEL) |                   |
| Reference group                  | Workers (professional)         |                   |
| Duration of exposure             | Long-term                      |                   |
| Route of exposure                | inhalative                     |                   |
| Mode of action                   | Systemic effects               |                   |
| Concentration                    | 0,035                          | mg/m <sup>3</sup> |
|                                  |                                |                   |
| Type of value                    | Derived No Effect Level (DNEL) |                   |
| Reference group                  | Workers (professional)         |                   |
| Duration of exposure             | Long-term                      |                   |
| Route of exposure                | inhalative                     |                   |
| Mode of action                   | Local effects                  |                   |
| Concentration                    | 0,035                          | mg/m <sup>3</sup> |

**Predicted No Effect Concentration (PNEC)**

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

**n-butyl acetate**

|               |                              |       |
|---------------|------------------------------|-------|
| Type of value | PNEC                         |       |
| Type          | Freshwater                   |       |
| Concentration | 0,18                         | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Saltwater                    |       |
| Concentration | 0,018                        | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Sewage treatment plant (STP) |       |
| Concentration | 35,6                         | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Water                        |       |
| Conditions    | sporadic release             |       |
| Concentration | 0,36                         | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Fresh water sediment         |       |
| Concentration | 0,981                        | mg/kg |
| Type of value | PNEC                         |       |
| Type          | saltwater sediment           |       |
| Concentration | 0,0981                       | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Soil                         |       |
| Concentration | 0,0903                       | mg/kg |

**4-methylpentan-2-one**

|               |                              |       |
|---------------|------------------------------|-------|
| Type of value | PNEC                         |       |
| Type          | Freshwater                   |       |
| Concentration | 0,6                          | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Saltwater                    |       |
| Concentration | 0,06                         | mg/l  |
| Type of value | PNEC                         |       |
| Conditions    | sporadic release             |       |
| Concentration | 1,5                          | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Sewage treatment plant (STP) |       |
| Concentration | 27,5                         | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Fresh water sediment         |       |
| Concentration | 8,27                         | mg/kg |
| Type of value | PNEC                         |       |
| Type          | saltwater sediment           |       |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|               |      |       |
|---------------|------|-------|
| Concentration | 0,83 | mg/kg |
| Type of value | PNEC |       |
| Type          | Soil |       |
| Concentration | 1,3  | mg/kg |

**ethyl acetate**

|               |           |      |
|---------------|-----------|------|
| Type of value | PNEC      |      |
| Type          | Saltwater |      |
| Concentration | 0,026     | mg/l |

|               |            |      |
|---------------|------------|------|
| Type of value | PNEC       |      |
| Type          | Freshwater |      |
| Concentration | 0,26       | mg/l |

|               |      |       |
|---------------|------|-------|
| Type of value | PNEC |       |
| Type          | Soil |       |
| Concentration | 0,24 | mg/kg |

|               |                              |      |
|---------------|------------------------------|------|
| Type of value | PNEC                         |      |
| Type          | Sewage treatment plant (STP) |      |
| Concentration | 650                          | mg/l |

|               |                    |       |
|---------------|--------------------|-------|
| Type of value | PNEC               |       |
| Type          | saltwater sediment |       |
| Concentration | 0,125              | mg/kg |

|               |                      |       |
|---------------|----------------------|-------|
| Type of value | PNEC                 |       |
| Type          | Fresh water sediment |       |
| Concentration | 1,25                 | mg/kg |

|               |                  |      |
|---------------|------------------|------|
| Type of value | PNEC             |      |
| Conditions    | sporadic release |      |
| Concentration | 1,65             | mg/l |

**m-Tolyldiene diisocyanate**

|               |            |      |
|---------------|------------|------|
| Type of value | PNEC       |      |
| Type          | Freshwater |      |
| Concentration | 0,013      | mg/l |

|               |           |      |
|---------------|-----------|------|
| Type of value | PNEC      |      |
| Type          | Saltwater |      |
| Concentration | 0,00125   | mg/l |

|               |      |       |
|---------------|------|-------|
| Type of value | PNEC |       |
| Type          | Soil |       |
| Concentration | > 1  | mg/kg |

|               |                              |       |
|---------------|------------------------------|-------|
| Type of value | PNEC                         |       |
| Type          | Sewage treatment plant (STP) |       |
| Concentration | > 1                          | mg/kg |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7 mm

Breakthrough time  $\geq$  30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                        |                |
|------------------------|----------------|
| <b>Form</b>            | liquid         |
| <b>Colour</b>          | colourless     |
| <b>Odour</b>           | solvent-like   |
| <b>Odour threshold</b> |                |
| Remarks                | not determined |
| <b>pH value</b>        |                |
| Remarks                | not determined |
| <b>Melting point</b>   |                |
| Remarks                | not determined |
| <b>Freezing point</b>  |                |
| Remarks                | not determined |

### Initial boiling point and boiling range

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

Value 74 to 128 °C

**Flash point**

Value 13 °C

**Evaporation rate**

Remarks not determined

**Flammability (solid, gas)**

not determined

**Upper/lower flammability or explosive limits**

Remarks not determined

**Vapour pressure**

Remarks not determined

**Vapour density**

Remarks not determined

**Density**Value apprx. 1,041 kg/l  
Temperature 20 °C**Solubility in water**

Remarks not determined

**Solubility(ies)**

Remarks not determined

**Partition coefficient: n-octanol/water**

Remarks not determined

**Ignition temperature**

Remarks not determined

**Decomposition temperature**

Remarks not determined

**Viscosity**

Remarks not determined

**Efflux time**Value 25 to 30 s  
Temperature 20 °C  
Method DIN 53211 4 mm**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**9.2. Other information****Non-volatile content**Value 49,1 %  
Method calculated value**Other information**

This information is not available.

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

## 10. Stability and reactivity

### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

### 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts slowly with water resulting in evolution of carbon dioxide. Gaseous decomposition products cause pressure to build up in tightly sealed vessels. Precautions should be taken to minimise exposure to atmospheric humidity or water: CO<sub>2</sub> will be formed which in closed containers can result in pressurisation.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, hydrocyanic acid, Stable under recommended storage and handling conditions (see section 7).

## 11. Toxicological information

### 11.1. Information on toxicological effects

#### Acute oral toxicity

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

#### Acute dermal toxicity

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

#### Acute inhalational toxicity

|                     |   |      |
|---------------------|---|------|
| ATE                 | 6,9319  | mg/l |
| Administration/Form | Dust/Mist   |      |
| Method              | calculated value (Regulation (EC) No. 1272/2008)                  |      |
| Remarks             | Based on available data, the classification criteria are not met. |      |

#### Acute inhalative toxicity (Components)

##### 4-methylpentan-2-one

|                      |                                |   |      |
|----------------------|--------------------------------|---|------|
| Species              | rat                            |   |      |
| LC50                 | 2,9                            |   | mg/l |
| Duration of exposure | 4                              | h |      |
| Administration/Form  | Dust/Mist                      |   |      |
| Source               | 2 (reliable with restrictions) |   |      |

##### m-Tolylidene diisocyanate

|                      |       |   |      |
|----------------------|-------|---|------|
| Species              | rat   |   |      |
| LC50                 | 0,101 |   | mg/l |
| Duration of exposure | 4     | h |      |



Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

Administration/Form Dust/Mist

**Skin corrosion/irritation**

Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Skin corrosion/irritation (Components)****m-Tolyldiene diisocyanate**

evaluation Irritating to skin.

**Serious eye damage/irritation**

evaluation irritant  
 Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks The classification criteria are met.

**Serious eye damage/irritation (Components)****4-methylpentan-2-one**

Species rabbit  
 Observation Period 72 h  
 evaluation Irritating to eyes and respiratory system.  
 Source 1 (reliable without restriction)

**ethyl acetate**

Species rabbit  
 Observation Period 24 h  
 evaluation Irritating to eyes.  
 Source 2 (reliable with restrictions)

**polyisocyanate, aromatic**

Species rabbit  
 evaluation Irritating to eyes.

**Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidenetrimethanol**

Species rabbit  
 evaluation Irritating to eyes.

**m-Tolyldiene diisocyanate**

evaluation Irritating to eyes.

**Sensitization**

evaluation May cause sensitization by inhalation.  
 Method Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks The classification criteria are met.

**Sensitization (Components)****polyisocyanate, aromatic**

evaluation May cause sensitization by skin contact.

**Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidenetrimethanol**

Species guinea pig  
 evaluation May cause sensitization by skin contact.  
 Source Toxikologische Untersuchungen an einem vergleichbaren Produkt.

**m-Tolyldiene diisocyanate**

Species mouse  
 evaluation May cause sensitization by skin contact.

**m-Tolyldiene diisocyanate**

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

Route of exposure            inhalative  
 Species                        guinea pig  
 evaluation                      May cause sensitization by inhalation.

**Mutagenicity**

Method                         Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks                        Based on available data, the classification criteria are not met.

**Mutagenicity (Components)****m-Tolylidene diisocyanate**

Species                         Salmonella typhimurium  
 evaluation                      Not mutagenic in Ames Test.

**Reproductive toxicity**

Method                         Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks                        Based on available data, the classification criteria are not met.

**Reproduction toxicity (Components)****m-Tolylidene diisocyanate**

Route of exposure            inhalative  
 Species                         rat  
 Dose                              0,5                      ppm(m)  
 Duration of exposure        21                        d  
 evaluation                      No toxicity to reproduction  
 Remarks                        NOAEL

**Carcinogenicity**

Method                         Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks                        Based on available data, the classification criteria are not met.

**Carcinogenicity (Components)****m-Tolylidene diisocyanate**

evaluation                      Suspected of causing cancer.

**Specific Target Organ Toxicity (STOT)****Single exposure**

Method                         Calculation method (Regulation (EC) No. 1272/2008)  
 Remarks                        The classification criteria are met.  
 evaluation                      May cause drowsiness or dizziness.

**Repeated exposure**

Remarks                        Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT) (Components)****4-methylpentan-2-one**

evaluation                      May cause respiratory irritation.  
 Route of exposure Inhalation exposure  
 Organs: Nose, respiratory system, eyes  
 Remarks                        May cause respiratory irritation.

**ethyl acetate****Specific target organ toxicity - single exposure**

Remarks                        Organs: Nervous system  
 Possible narcotic effects (drowsiness, dizziness).

**n-butyl acetate****Specific target organ toxicity - repeated exposure**

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

Remarks  
Organs: Nervous system  
Possible narcotic effects (drowsiness, dizziness).

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other information**

No toxicological data are available.

**12. Ecological information****12.1. Toxicity****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Daphnia toxicity (Components)****m-Tolylidene diisocyanate**

|                      |                            |      |
|----------------------|----------------------------|------|
| Species              | Daphnia magna (Water flea) |      |
| EC50                 | 12,5                       | mg/l |
| Duration of exposure | 48                         | h    |
| Method               | OECD Test Guideline 202    |      |

**12.2. Persistence and degradability****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Biodegradability (Components)****m-Tolylidene diisocyanate**

|                             |     |   |
|-----------------------------|-----|---|
| Value                       | 0,0 | % |
| Duration of test evaluation | 28  | d |
| Not readily biodegradable.  |     |   |

**12.3. Bioaccumulative potential****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Partition coefficient: n-octanol/water**

Remarks not determined

**12.4. Mobility in soil****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Mobility in soil**

no data available

**12.5. Results of PBT and vPvB assessment****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**12.6. Other adverse effects****General information**

For this subsection there is no ecotoxicological data available on the product as such.

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

**General information / ecology**

For this subsection there is no ecotoxicological data available on the product as such.

**13. Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations for the product**

|                |  |
|----------------|--|
| EWC waste code | 080111 - waste paint and varnish containing organic solvents or other dangerous substances |
| EWC waste code | 200127 - paint, inks, adhesives and resins containing dangerous substances                 |

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

**modified product**

|                |  |
|----------------|--|
| EWC waste code | 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances |
| EWC waste code | 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances               |

**Dried residues**

|                |   |
|----------------|---|
| EWC waste code | 080112 - waste lacquers and waste paint except those falling under 080111 |
|----------------|---|

**Disposal recommendations for packaging**

|                |   |
|----------------|---|
| EWC waste code | 150110 - packaging containing residues of or contaminated by dangerous substances |
|----------------|---|

Completely emptied packagings can be given for recycling.

Completely emptied packagings can be given for recycling.

**14. Transport information**




Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|                                  | Land transport ADR/RID  | Marine transport IMDG/GGVSee   | Air transport ICAO/IATA   |
|----------------------------------|---|--|---|
| Tunnel restriction code          | D/E   |  |   |
| 14.1. UN number                  | 1263  | 1263   | 1263  |
| 14.2. UN proper shipping name    | PAINT   | PAINT  | PAINT   |
| 14.3. Transport hazard class(es) | 3   | 3  | 3   |
| Label                            |  |  |  |
| 14.4. Packing group              | II  | II   | II  |
| Special provision                | 640D  |  |   |
| Limited Quantity                 | 5 l   |  |   |
| Transport category               | 2   |  |   |

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU) 51 % 530 g/l

#### Other information

All components are contained in the TSCA inventory or exempted.  
 All components are contained in the PICCS inventory.  
 All components are contained in the IECSC inventory.  
 All components are contained in the ENCS inventory.  
 All components are contained in the ECL inventory.

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## 16. Other information

### Hazard statements listed in Chapter 3

|        |   |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H225   | Highly flammable liquid and vapour.                   |
| H226   | Flammable liquid and vapour.                          |
| H315   | Causes skin irritation.                               |
| H317   | May cause an allergic skin reaction.                  |
| H319   | Causes serious eye irritation.                        |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|      |  |
|------|--|
| H330 | Fatal if inhaled.  |
| H332 | Harmful if inhaled.  |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation.  |
| H336 | May cause drowsiness or dizziness.   |
| H351 | Suspected of causing cancer.   |
| H412 | Harmful to aquatic life with long lasting effects.                         |

**CLP categories listed in Chapter 3**

|                   |  |
|-------------------|--|
| Acute Tox. 2      | Acute toxicity, Category 2                                   |
| Acute Tox. 4      | Acute toxicity, Category 4                                   |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic, Category 3    |
| Carc. 2           | Carcinogenicity, Category 2                                  |
| Eye Irrit. 2      | Eye irritation, Category 2                                   |
| Flam. Liq. 2      | Flammable liquid, Category 2                                 |
| Flam. Liq. 3      | Flammable liquid, Category 3                                 |
| Resp. Sens. 1     | Respiratory sensitization, Category 1                        |
| Skin Irrit. 2     | Skin irritation, Category 2                                  |
| Skin Sens. 1      | Skin sensitization, Category 1                               |
| STOT SE 3         | Specific target organ toxicity - single exposure, Category 3 |

**Abbreviations**

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IMDG - International Maritime Code for Dangerous Goods  
 IATA - International Air Transport Association  
 IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
 GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS - European Inventory of Existing Commercial Chemical Substances  
 CAS - Chemical Abstracts Service (division of the American Chemical Society)  
 GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
 LOAEL - Lowest Observed Adverse Effect Level  
 LOEL - Lowest Observed Effect Level  
 NOAEL - No Observed Adverse Effect Level  
 NOEC - No Observed Effect Concentration  
 NOEL - No Observed Effect Level  
 OECD - Organisation for Economic Cooperation and Development  
 VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*\*) . This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES001 - Industrial applications: industrial spraying (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

|       |  |
|-------|--|
| SU3   | Industrial uses: Uses of substances as such or in preparations at industrial sites         |
| ERC4  | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC5  | Industrial use resulting in inclusion into or onto a matrix                                |
| PROC7 | Industrial spraying  |

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

|      |  |
|------|--|
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC5 | Industrial use resulting in inclusion into or onto a matrix                                |

### **Physical form**

liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 300

### **Other relevant operational conditions**

Use: Room temperature  
 Drying and through-curing takes place at ambient temperature or at higher temperatures.  
 Where possible recycling is preferred to disposal or incineration.  
 Do not allow to enter soil, waterways or waste water canal.  
 Dispose of rinse water in accordance with local and national regulations.

### **Waste water**

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

### **Exhaust air**

Keep container closed. Avoid release to the environment.

### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

### **Disposal recommendations for the product**

|                |  |
|----------------|--|
| EWC waste code | 080111 - waste paint and varnish containing organic solvents or other dangerous substances |
|                | 200127 - paint, inks, adhesives and resins containing dangerous substances                 |

Where possible recycling is preferred to disposal or incineration.  
 Do not allow to enter drains or waterways.  
 Where possible recycling is preferred to disposal or incineration.  
 Do not allow to enter drains or waterways.

### **modified product**

|                |  |
|----------------|--|
| EWC waste code | 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances |
|----------------|--|

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

080113 - sludges from paint or varnish containing organic solvents or other dangerous substances

**Dried residues**

EWC waste code

080112 - waste lacquers and waste paint except those falling under 080111

**Disposal recommendations for packaging**

EWC waste code

150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

Completely emptied packagings can be given for recycling.

**Contributing exposure scenario controlling worker exposure****Use**

SU3

Industrial uses: Uses of substances as such or in preparations at industrial sites

PROC7

Industrial spraying

**Physical form**

liquid

**Maximum amount used per time or activity**

Duration of exposure

&lt;= 8 h/d

Frequency of exposure

&lt;= 220 d/a

**Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Read attached instructions before use.

**Product substance and product safety related measures**

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

**Hand protection**

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness &gt;= 0,7

Breakthrough time &gt;= 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor



Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

maintenance.

**Eye protection**

Wear eye glasses with side protection according to EN 166.

**Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

**Exposure estimation and reference to its source**

**Workers (industrial)**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU3                              |
| PROC                              | PROC7                            |
| Assessment method                 | inhalation, long-term - systemic |
|                                   | Indoor use                       |
| Risk characterisation ratio (RCR) | 0,75                             |
| Lead substance                    | 4-methylpentan-2-one             |

**Workers (industrial)**

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU3                          |
| PROC                              | PROC7                        |
| Assessment method                 | dermal, long-term - systemic |
|                                   | Indoor use                   |
| Risk characterisation ratio (RCR) | 0,5                          |
| Lead substance                    | 4-methylpentan-2-one         |

**Workers (industrial)**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU3                              |
| PROC                              | PROC10                           |
| Assessment method                 | inhalation, long-term - systemic |
|                                   | Indoor use                       |
| Risk characterisation ratio (RCR) | 0,5                              |
| Lead substance                    | 4-methylpentan-2-one             |

**Workers (industrial)**

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU3                          |
| PROC                              | PROC10                       |
| Assessment method                 | dermal, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,5                          |
| Lead substance                    | 4-methylpentan-2-one         |

**Workers (industrial)**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU3                              |
| PROC                              | PROC13                           |
| Assessment method                 | inhalation, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,5                              |
| Lead substance                    | 4-methylpentan-2-one             |

**Workers (industrial)**

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU3                          |
| PROC                              | PROC13                       |
| Assessment method                 | dermal, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,5                          |
| Lead substance                    | 4-methylpentan-2-one         |

**Information on estimated exposure and downstream-user guidance**

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

### Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

## Annex to the extended Safety Data Sheet (eSDS)

### Short title of the exposure scenario

ES003 - Professional uses: Non industrial spraying (inside)

### Use of the substance/preparation

Surface treatment of wood and other materials

### Use

|        |  |
|--------|--|
| SU22   | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a  | Wide dispersive indoor use of processing aids in open systems                                    |
| ERC8c  | Wide dispersive indoor use resulting in inclusion into or onto a matrix                          |
| PROC11 | Non industrial spraying  |

## Contributing exposure scenario controlling environmental exposure

### Use

|       |   |
|-------|---|
| ERC8a | Wide dispersive indoor use of processing aids in open systems           |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |

### Physical form

liquid

### Maximum amount used per time or activity

Emission days per site: <= 250

### Other relevant operational conditions

Use: Room temperature  
 Drying and through-curing takes place at ambient temperature or at higher temperatures.  
 Volatile organic substances will volatilise into the atmospheric air inside.  
 Where possible recycling is preferred to disposal or incineration.  
 Do not allow to enter soil, waterways or waste water canal.  
 Dispose of rinse water in accordance with local and national regulations.

### Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

### Exhaust air

Keep container closed. Avoid release to the environment.

### Soil

Floors should be impervious, resistant to liquids and easy to clean.

### Disposal recommendations for the product

|                |  |
|----------------|--|
| EWC waste code | 080111 - waste paint and varnish containing organic solvents or other dangerous substances |
|                | 200127 - paint, inks, adhesives and resins containing dangerous substances                 |

Where possible recycling is preferred to disposal or incineration.  
 Do not allow to enter drains or waterways.  
 Where possible recycling is preferred to disposal or incineration.

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

Do not allow to enter drains or waterways.

**modified product**

EWC waste code

080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances  
080113 - sludges from paint or varnish containing organic solvents or other dangerous substances

**Dried residues**

EWC waste code

080112 - waste lacquers and waste paint except those falling under 080111

**Disposal recommendations for packaging**

EWC waste code

150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

Completely emptied packagings can be given for recycling.

**Contributing exposure scenario controlling worker exposure (professional)****Short title of the exposure scenario**

Substance number:CES006

**Use**

SU22

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC11

Non industrial spraying

**Physical form**

liquid

**Maximum amount used per time or activity**

Duration of exposure &lt;= 8 h/d

Frequency of exposure &lt;= 220 d/a

**Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Volatile organic substances will volatilise into the atmospheric air inside.

Read attached instructions before use.

**Product substance and product safety related measures**

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

**Hand protection**

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness &gt;= 0,7

Breakthrough time &gt;= 30

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (professional)

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU22                             |
| PROC                              | PROC10                           |
| Assessment method                 | inhalation, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,5                              |
| Lead substance                    | 4-methylpentan-2-one             |

### Workers (professional)

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU22                         |
| PROC                              | PROC10                       |
| Assessment method                 | dermal, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,1                          |
| Lead substance                    | 4-methylpentan-2-one         |

### Workers (professional)

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU22                             |
| PROC                              | PROC11                           |
| Assessment method                 | inhalation, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,5                              |
| Lead substance                    | 4-methylpentan-2-one             |

### Workers (professional)

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU22                         |
| PROC                              | PROC11                       |
| Assessment method                 | dermal, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,5                          |
| Lead substance                    | 4-methylpentan-2-one         |

### Workers (professional)

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU22                             |
| PROC                              | PROC13                           |
| Assessment method                 | inhalation, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,75                             |
| Lead substance                    | 4-methylpentan-2-one             |

### Workers (professional)

|      |        |
|------|--------|
| SU   | SU22   |
| PROC | PROC13 |

Trade name: Hesse PU Hardener DR 4040

Version: 19 / GB

Revision: 06.08.2020

Replaces Version: 18 / GB

Print date: 27.08.20

|                                   |                              |
|-----------------------------------|------------------------------|
| Assessment method                 | dermal, long-term - systemic |
| Risk characterisation ratio (RCR) | 0,5                          |
| Lead substance                    | 4-methylpentan-2-one         |

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.