

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse HYDRO Hardener HDR 5091

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	REACHSET 1003
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)	
Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Sens. 1	H317
STOT SE 3	H335
STOT SE 3	H336

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

#### Hazard pictograms

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23



### Signal word

Warning

### Hazard statements

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains	n,n-dimethylcyclohexylamine; polyisocyanate, aliphatic; hexamethylene diisocyanate, oligomers; 1,6-hexamethylene diisocyanate homopolymer
----------	---

### Supplemental information

EUH204	Contains isocyanates. May produce an allergic reaction.
--------	---

### 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### 1,6-hexamethylene diisocyanate homopolymer

CAS No.	28182-81-2			
EINECS no.	500-060-2			
Registration no.	01-2119485796-17			
Concentration	>= 25	< 50		%
Classification (Regulation (EC) No. 1272/2008)	Acute Tox. 4	H332		Route of exposure: Inhalation exposure
	Skin Sens. 1	H317		
	STOT SE 3	H335		Respiratory tract

ATE	Inhalation exposure, Dust/Mist	2,81	mg/l
-----	--------------------------------	------	------

#### 2-methoxy-1-methylethyl acetate

CAS No.	108-65-6
---------	----------

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

EINECS no. 203-603-9  
 Registration no. 01-2119475791-29  
 Concentration  $\geq$  25 < 50 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Flam. Liq. 3 H226  
 STOT SE 3 H336

**hexamethylene diisocyanate, oligomers**

CAS No. 28182-81-2  
 EINECS no. 500-060-2  
 Registration no. 01-2119488934-20  
 Concentration  $\geq$  20 < 25 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Acute Tox. 4 H332 Route of exposure: Inhalation exposure  
 Skin Sens. 1 H317  
 STOT SE 3 H335

ATE Inhalation exposure, Dust/Mist 1,5 mg/l

**polyisocyanate, aliphatic**

CAS No. 666723-27-9  
 Concentration  $\geq$  1 < 10 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Acute Tox. 4 H332 Route of exposure: Inhalation exposure  
 Skin Sens. 1B H317  
 STOT SE 3 H335  
 Aquatic Chronic 3 H412

ATE Inhalation exposure, Dust/Mist 1,5 mg/l

**n,n-dimethylcyclohexylamine**

CAS No. 98-94-2  
 EINECS no. 202-715-5  
 Registration no. 01-2119533030-60  
 Concentration  $\geq$  0,1 < 0,9 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Flam. Liq. 3 H226  
 Met. Corr. 1 H290  
 Acute Tox. 3 H301 Route of exposure: Oral exposure  
 Acute Tox. 3 H311 Route of exposure: Dermal exposure  
 Acute Tox. 3 H331 Route of exposure: Inhalation exposure  
 Skin Corr. 1B H314  
 Eye Dam. 1 H318  
 Aquatic Chronic 2 H411

ATE Oral exposure 272 mg/kg  
 ATE Dermal exposure 380 mg/kg  
 ATE Inhalation exposure, Dust/Mist 0,7 mg/l

**Hexamethylene-di-isocyanate**

CAS No. 822-06-0  
 EINECS no. 212-485-8

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Registration no.	01-2119457571-37		
Concentration		< 0,1	%
Classification (Regulation (EC) No. 1272/2008)			
Acute Tox. 4	H302		Route of exposure: Oral exposure
Acute Tox. 1	H330		Route of exposure: Inhalation exposure
Eye Irrit. 2	H319		
STOT SE 3	H335		
Skin Irrit. 2	H315		
Resp. Sens. 1	H334		
Skin Sens. 1	H317		
Concentration limits (Regulation (EC) No. 1272/2008)			
Resp. Sens. 1	H334	>= 0,5 %	
Skin Sens. 1	H317	>= 0,5 %	

**Note**

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitisation of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically.

## SECTION 5: Firefighting measures

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

## 5.1. Extinguishing media

### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

## 5.2. Special hazards arising from the substance or mixture

Vapours can form an explosive mixture with air.

## 5.3. Advice for firefighters

### Other information

Standard procedure for chemical fires.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this mixture is used. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge.

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Keep away from oxidising agents, strongly alkaline and strongly acid materials, amines, alcohols and water.

### Storage classes

Storage class according to TRGS 510      3                      Flammable liquid

### Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## 7.3. Specific end use(s)

See exposure scenario, if available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### 2-methoxy-1-methylethyl acetate

List	Directive 2017/164 EG			
Value	275	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	550	mg/m <sup>3</sup>	100	ppm(V)
Status:	12/2009			

##### 2-methoxy-1-methylethyl acetate

List	EH40			
Value	274	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	548	mg/m <sup>3</sup>	100	ppm(V)
Skin resorption / sensibilisation:	Sk; Status: 01/2020			

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### 2-methoxy-1-methylethyl acetate

Type of value	Derived No Effect Level (DNEL)		
Reference group	Workers (professional)		
Duration of exposure	Long-term		
Route of exposure	inhalative		
Mode of action	Systemic effects		
Concentration	275		mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)		
Reference group	Workers (professional)		
Duration of exposure	Long-term		
Route of exposure	Dermal exposure		

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Mode of action	Systemic effects	
Concentration	153,5	mg/kg/d

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Oral exposure
-------------------	---------------

Mode of action	Systemic effects
----------------	------------------

Concentration	1,67	mg/kg/d
---------------	------	---------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Systemic effects
----------------	------------------

Concentration	33	mg/m <sup>3</sup>
---------------	----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Dermal exposure
-------------------	-----------------

Mode of action	Systemic effects
----------------	------------------

Concentration	54,8	mg/kg
---------------	------	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Worker
-----------------	--------

Duration of exposure	Acute
----------------------	-------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	550	mg/m <sup>3</sup>
---------------	-----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	33	mg/m <sup>3</sup>
---------------	----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Acute
----------------------	-------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	33	mg/m <sup>3</sup>
---------------	----	-------------------

**Hexamethylene-di-isocyanate**

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Workers (professional)
-----------------	------------------------

Duration of exposure	Short-term
----------------------	------------

Route of exposure	inhalative
-------------------	------------

Mode of action	Systemic effects
----------------	------------------

Concentration	0,07	mg/m <sup>3</sup>
---------------	------	-------------------

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	0,035	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,035	mg/m <sup>3</sup>

**hexamethylene diisocyanate, oligomers**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	1	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,5	mg/m <sup>3</sup>

**1,6-hexamethylene diisocyanate homopolymer**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	1	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,5	mg/m <sup>3</sup>

**Predicted No Effect Concentration (PNEC)**

**2-methoxy-1-methylethyl acetate**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,635	mg/l

Type of value	PNEC	
Type	Saltwater	



Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Concentration	0,0635	mg/l
Type of value	PNEC	
Conditions	sporadic release	
Concentration	6,35	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	3,29	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,329	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,29	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

**Hexamethylene-di-isocyanate**

Type of value	PNEC	
Type	Freshwater	
Concentration	> 0,0774	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	> 0,00774	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	> 0,01334	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	> 0,001334	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	> 0,0026	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	8,42	mg/l

**hexamethylene diisocyanate, oligomers**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,199	mg/l
Type of value	PNEC	

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Type	Saltwater		
Concentration	0,0199		mg/l
Type of value	PNEC		
Type	Fresh water sediment		
Concentration	44551		mg/kg
Type of value	PNEC		
Type	saltwater sediment		
Concentration	4455		mg/kg
Type of value	PNEC		
Type	Soil		
Concentration	8884		mg/kg
Type of value	PNEC		
Type	Sewage treatment plant (STP)		
Concentration	100		mg/l
<b>1,6-hexamethylene diisocyanate homopolymer</b>			
Type of value	PNEC		
Type	Freshwater		
Concentration	0,127		mg/l
Type of value	PNEC		
Type	marine water		
Concentration	0,0127		mg/l
Type of value	PNEC		
Type	Fresh water sediment		
Concentration	266,7		g/kg
Type of value	PNEC		
Type	saltwater sediment		
Concentration	4,455		g/kg
Type of value	PNEC		
Type	Soil		
Concentration	53,2		g/kg
Type of value	PNEC		
Type	Sewage treatment plant (STP)		
Concentration	38,28		mg/l

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7 mm

Breakthrough time  $\geq$  30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	liquid
<b>Colour</b>	colourless
<b>Odour</b>	characteristic
<b>Melting point</b>	
Remarks	not determined
<b>Freezing point</b>	
Remarks	not determined
<b>Boiling point or initial boiling point and boiling range</b>	
Value	145,8 to 161 °C
<b>Flammability</b>	not determined
<b>Upper and lower explosive limits</b>	
Remarks	not determined
<b>Flash point</b>	
Value	44 °C
<b>Ignition temperature</b>	
Remarks	not determined
<b>Decomposition temperature</b>	
Remarks	not determined

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

**pH value**

Remarks Not applicable

**Viscosity**

Remarks not determined

**Solubility(ies)**

Remarks not determined

**Partition coefficient n-octanol/water (log value)**

Remarks not determined

**Vapour pressure**

Remarks not determined

**Density and/or relative density**

Value appr. 1,094 kg/l  
Temperature 20 °C

**Relative vapour density**

Remarks not determined

**Particle characteristics**

Remarks not determined

**9.2. Other information**

**Odour threshold**

Remarks not determined

**Evaporation rate**

Remarks not determined

**Solubility in water**

Remarks not determined

**Efflux time**

Value 26 to 28 s  
Temperature 20 °C  
Method DIN 53211 4 mm

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**Non-volatile content**

Value 69,4 %  
Method calculated value

**Other information**

This information is not available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

### 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts slowly with water resulting in evolution of carbon dioxide. Gaseous decomposition products cause pressure to build up in tightly sealed vessels. Precautions should be taken to minimise exposure to atmospheric humidity or water: CO<sub>2</sub> will be formed which in closed containers can result in pressurisation.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, hydrocyanic acid, Stable under recommended storage and handling conditions (see section 7).

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		
Remarks	Based on available data, the classification criteria are not met.		

#### Acute oral toxicity (Components)

##### Hexamethylene-di-isocyanate

Species	rat		
LD50		746	mg/kg
Method	OECD 401		

##### n,n-dimethylcyclohexylamine

Species	rat		
LD50		272	mg/kg

#### Acute dermal toxicity

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		
Remarks	Based on available data, the classification criteria are not met.		

#### Acute dermal toxicity (Components)

##### n,n-dimethylcyclohexylamine

Species	rat		
LD50		380	mg/kg

#### Acute inhalational toxicity

ATE		2,811	mg/l
Administration/Form	Dust/Mist		
Method	calculated value (Regulation (EC) No. 1272/2008)		
Remarks	The classification criteria are met.		

#### Acute inhalative toxicity (Components)

polyisocyanate, aliphatic

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

ATE	1,5		mg/l
Duration of exposure	4	h	
Administration/Form	Dust/Mist		
Method	conversion value		

**n,n-dimethylcyclohexylamine**

Species	rat		
LC50	0,7		mg/l
Duration of exposure	4	h	
Administration/Form	Dust/Mist		

**hexamethylene diisocyanate, oligomers**

ATE	1,5		mg/l
Duration of exposure	4	h	
Administration/Form	Dust/Mist		
Method	conversion value		
Remarks	Mist		

**1,6-hexamethylene diisocyanate homopolymer**

Species	rat		
LC50	2,81		mg/l
Duration of exposure	4	h	
Administration/Form	Dust/Mist		
Remarks	Mist		

**Skin corrosion/irritation**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Skin corrosion/irritation (Components)**

**Hexamethylene-di-isocyanate**

Species	rabbit
evaluation	Severe skin irritation

**n,n-dimethylcyclohexylamine**

Species	rabbit
Observation Period	8 d
evaluation	Causes burns.

**Serious eye damage/irritation**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Serious eye damage/irritation (Components)**

**Hexamethylene-di-isocyanate**

Species	rabbit
---------	--------

**n,n-dimethylcyclohexylamine**

Species	rabbit
Duration of exposure	8 d
Observation Period	8 d

**Sensitization**

evaluation	May cause sensitization by skin contact.
Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	The classification criteria are met.

**Sensitization (Components)**

polyisocyanate, aliphatic

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Species mouse  
evaluation May cause sensitization by skin contact.

**hexamethylene diisocyanate, oligomers**

Species mouse  
evaluation May cause sensitization by skin contact.

**1,6-hexamethylene diisocyanate homopolymer**

evaluation May cause sensitization by skin contact.

**Mutagenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

**Carcinogenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)**

**Single exposure**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks The classification criteria are met.  
evaluation May cause respiratory irritation.  
evaluation May cause drowsiness or dizziness.

**Repeated exposure**

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT) (Components)**

**2-methoxy-1-methylethyl acetate**

**Specific target organ toxicity - repeated exposure**

evaluation May cause drowsiness or dizziness.  
Organs: Nervous system

**Hexamethylene-di-isocyanate**

**Specific target organ toxicity - single exposure**

evaluation May cause respiratory irritation.  
Organs: Respiratory tract

**polyisocyanate, aliphatic**

**Specific target organ toxicity - single exposure**

evaluation May cause respiratory irritation.  
Organs: Respiratory tract

**hexamethylene diisocyanate, oligomers**

**Specific target organ toxicity - single exposure**

evaluation May cause respiratory irritation.  
Route of exposure Inhalation exposure  
Organs: Respiratory tract

**1,6-hexamethylene diisocyanate homopolymer**

evaluation May cause respiratory irritation.  
Organs: Respiratory tract

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Other information

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### polyisocyanate, aliphatic

Species	Danio rerio (zebra fish)		
LC50	35,2		mg/l
Duration of exposure	96	h	
Method	OECD 203		

##### hexamethylene diisocyanate, oligomers

Species	Danio rerio (zebra fish)		
LC50	> 100		mg/l
Duration of exposure	96	h	
Method	OECD 203		

##### 1,6-hexamethylene diisocyanate homopolymer

Species	Danio rerio (zebra fish)		
LC50	35,2		mg/l
Duration of exposure	96	h	
Method	OECD 203		

#### Daphnia toxicity (Components)

##### hexamethylene diisocyanate, oligomers

Species	Daphnia magna (Water flea)		
EC50	> 100		mg/l
Duration of exposure	48	h	
Method	OECD 202, part 1, static		

##### 1,6-hexamethylene diisocyanate homopolymer

Species	Daphnia magna (Water flea)		
EC50	> 100		mg/l
Duration of exposure	48	h	

#### Algae toxicity (Components)

##### n,n-dimethylcyclohexylamine

Species	Scenedesmus subspicatus		
NOEC	0,062		mg/l
Duration of exposure	72	h	
Method	OECD 201		

##### hexamethylene diisocyanate, oligomers



Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Species	Scenedesmus subspicatus	
IC50	199	mg/l
Duration of exposure	72	h
Method	OECD 201	

**1,6-hexamethylene diisocyanate homopolymer**

Species	Desmodesmus subspicatus	
ErC50	72	mg/l
Duration of exposure	72	h
Method	OECD 201	

**Bacteria toxicity (Components)**

**hexamethylene diisocyanate, oligomers**

Species	activated sludge	
EC50	> 10000	mg/l

**1,6-hexamethylene diisocyanate homopolymer**

Species	activated sludge	
EC50	> 10000	mg/l

**12.2. Persistence and degradability**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Biodegradability (Components)**

**polyisocyanate, aliphatic**

Value	0,0	%
evaluation	Not readily biodegradable.	

**n,n-dimethylcyclohexylamine**

Value	appr. 100	%
Duration of test	28	d
evaluation	Readily biodegradable.	

**hexamethylene diisocyanate, oligomers**

Value	2	%
Duration of test	28	d
evaluation	Not readily biodegradable.	

**1,6-hexamethylene diisocyanate homopolymer**

Value	0,0	%
evaluation	Not readily biodegradable.	

**12.3. Bioaccumulative potential**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Partition coefficient n-octanol/water (log value)**

Remarks	not determined
---------	----------------

**12.4. Mobility in soil**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Mobility in soil**

no data available

**12.5. Results of PBT and vPvB assessment**

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Results of PBT and vPvB assessment

The product contains no PBT substances  
The product contains no vPvB substances.

## 12.6 Endocrine disrupting properties

### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## 12.7. Other adverse effects

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

#### modified product

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances

#### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

#### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

## SECTION 14: Transport information




Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Limited Quantity	5 l		
Transport category	3		

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU) 30,6 % 335 g/l

#### Other information

All components are contained in the TSCA inventory or exempted.

All components are contained in the IECSC inventory.

All components are contained in the ECL inventory.

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### CLP categories listed in Chapter 3

Acute Tox. 1	Acute toxicity, Category 1
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Met. Corr. 1	Substance or mixture corrosive to metals, Category 1
Resp. Sens. 1	Respiratory sensitization, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, Category 1B
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG - International Maritime Code for Dangerous Goods  
IATA - International Air Transport Association  
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS - European Inventory of Existing Commercial Chemical Substances  
CAS - Chemical Abstracts Service (division of the American Chemical Society)  
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL - Lowest Observed Adverse Effect Level  
LOEL - Lowest Observed Effect Level  
NOAEL - No Observed Adverse Effect Level  
NOEC - No Observed Effect Concentration  
NOEL - No Observed Effect Level  
OECD - Organisation for Economic Cooperation and Development  
VOC - Volatile Organic Compounds  
Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.  
The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.  
The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES002 - Industrial applications: rolling, dipping, pouring and other processing without aerosol formation (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROCh02	roller coating industrial
PROC13	Treatment of articles by dipping and pouring

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix

### **Physical form**

liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 300

### **Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

### **Waste water**

Do not discharge into the drains/surface waters/groundwater.

### **Exhaust air**

Keep container closed. Avoid release to the environment.

### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

### **Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
	200127 - paint, inks, adhesives and resins containing dangerous substances

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

#### modified product

EWC waste code 080115 - aqueous sludges containing paint or varnish  
containing organic solvents or other dangerous substances  
080113 - sludges from paint or varnish containing organic  
solvents or other dangerous substances

#### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling  
under 080111

#### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated  
by dangerous substances

Completely emptied packagings can be given for recycling.

### Contributing exposure scenario controlling worker exposure

#### Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
PROCh01 Other processing without aerosol formation  
PROCh02 roller coating industrial  
PROC13 Treatment of articles by dipping and pouring

#### Physical form

liquid

#### Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

#### Other relevant operational conditions

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Read attached instructions before use.

#### Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

#### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

#### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness >= 0,7

Breakthrough time >= 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	27,54 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,1
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	dermal, long-term - local and systemic
Exposure assessment	2,14 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,01
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	55,08 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,2
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	dermal, long-term - local and systemic
Exposure assessment	27,43 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,18
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC13
Assessment method	inhalation, long-term - local and systemic



Trade name: Hesse HYDRO Hardener HDR 5091

Version: 25 / GB

Revision: 28.11.2022

Replaces Version: 24 / GB

Print date: 17.03.23

Exposure assessment	55,08	mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,2	
Lead substance	2-methoxy-1-methylethyl acetate	

**Workers (industrial)**

SU	SU3	
PROC	PROC13	
Assessment method	dermal, long-term - local and systemic	
Exposure assessment	13,71	mg/kg/d
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,09	
Lead substance	2-methoxy-1-methylethyl acetate	

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.