

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Proterra COLOR-SOLID-OIL NERO

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)  
Skin Sens. 1 H317

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

##### Hazard pictograms



##### Signal word

Warning

##### Hazard statements

H317 May cause an allergic skin reaction.

##### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

P362+P364 Take off contaminated clothing and wash it before reuse.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains tung oil

**Supplemental information****Further supplemental information**

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

**2.3. Other hazards**

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

**3. Composition/information on ingredients****Hazardous ingredients****tung oil**

CAS No.	8001-20-5			
EINECS no.	232-272-3			
Concentration	>= 25	<	50	%
Classification (Regulation (EC) No. 1272/2008)	Skin Sens. 1		H317	

**Naphtha (petroleum), hydrotreated heavy**

CAS No.	64742-48-9			
EINECS no.	265-150-3			
Registration no.	01-2119457273-39			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)	Asp. Tox. 1		H304	

**hydrocarbons, C12-18**

EINECS no.	927-632-8			
Registration no.	01-2119457736-27			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)	Asp. Tox. 1		H304	
			EUH066	

**2-ethylhexanoic acid zirconium salt**

CAS No.	22464-99-9			
EINECS no.	245-018-1			
Registration no.	01-2119979088-21			
Concentration	>= 0,1	<	1	%
Classification (Regulation (EC) No. 1272/2008)	Repr. 2		H361d	

**Note**

For explanation of abbreviations see section 16.  
 This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

## 4. First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically.

## 5. Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Storage classes

Storage class according to TRGS 510      10      Flammable liquids

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

### 7.3. Specific end use(s)

See exposure scenario, if available.

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### 2-ethylhexanoic acid zirconium salt

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32,97	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	6,49	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	4,51	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	8,13	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	3,25	mg/kg/d

#### Predicted No Effect Concentration (PNEC)

##### 2-ethylhexanoic acid zirconium salt

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

Type of value	PNEC		
Type	Freshwater		
Concentration	0,36		mg/l
Type of value	PNEC		
Type	Saltwater		
Concentration	0,036		mg/l
Type of value	PNEC		
Type	Fresh water sediment		
Concentration	6,37		mg/kg
Type of value	PNEC		
Type	saltwater sediment		
Concentration	0,637		mg/kg
Type of value	PNEC		
Type	Soil		
Concentration	1,06		mg/kg
Type of value	PNEC		
Type	Sewage treatment plant (STP)		
Concentration	71,7		mg/kg

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Respiratory protection not applicable; Use breathing apparatus if exposed to vapours/dust/aerosol.  
 Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material Nitrile rubber

Material thickness  $\geq$  0,4 mm

Breakthrough time  $\geq$  30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

Wear eye glasses with side protection according to EN 166.

**Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

**9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Form</b>	liquid		
<b>Colour</b>	white		
<b>Odour</b>	characteristic		
<b>Odour threshold</b>			
Remarks	not determined		
<b>pH value</b>			
Remarks	not determined		
<b>Melting point</b>			
Remarks	not determined		
<b>Freezing point</b>			
Remarks	not determined		
<b>Initial boiling point and boiling range</b>			
Remarks	not determined		
<b>Flash point</b>			
Value	> 60		°C
<b>Evaporation rate</b>			
Remarks	not determined		
<b>Flammability (solid, gas)</b>			
not determined			
<b>Upper/lower flammability or explosive limits</b>			
Remarks	not determined		
<b>Vapour pressure</b>			
Remarks	not determined		
<b>Vapour density</b>			
Remarks	not determined		
<b>Density</b>			
Value	appr. 1,015		kg/l
Temperature	20	°C	
<b>Solubility in water</b>			
Remarks	not determined		
<b>Solubility(ies)</b>			
Remarks	not determined		
<b>Partition coefficient: n-octanol/water</b>			
Remarks	not determined		
<b>Ignition temperature</b>			
Remarks	not determined		

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

**Decomposition temperature**

Remarks not determined

**Viscosity**

Remarks not determined

**Efflux time**

Value	40	to	90	s
Temperature	20	°C		
Method	DIN 53211 4 mm			

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**9.2. Other information****Non-volatile content**

Value	83,9	%
Method	calculated value	

**Other information**

This information is not available.

**10. Stability and reactivity****10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

**10.4. Conditions to avoid**

Isolate from sources of heat, sparks and open flame.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6. Hazardous decomposition products**Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.**11. Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Acute dermal toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
--------	--



Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

Remarks Based on available data, the classification criteria are not met.

**Acute inhalational toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Skin corrosion/irritation**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Serious eye damage/irritation**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Sensitization**

evaluation May cause sensitization by skin contact.

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks The classification criteria are met.

**Sensitization (Components)****tung oil**

evaluation May cause sensitization by skin contact.

**Mutagenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Reproduction toxicity (Components)****2-ethylhexanoic acid zirconium salt**

evaluation Toxic to Reproduction Category 2

**Carcinogenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)****Single exposure**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Repeated exposure**

Remarks Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other information**

No toxicological data are available.

**12. Ecological information****12.1. Toxicity****General information**

For this subsection there is no ecotoxicological data available on the product as such.

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

**Fish toxicity (Components)****hydrocarbons, C12-18**

LC50	>	1028		mg/l
Duration of exposure		96	h	

**hydrocarbons, C12-18**

Species		Oncorhynchus mykiss (rainbow trout)		
NOEC	>	10000		mg/l
Duration of exposure		31	Weeks	

**Daphnia toxicity (Components)****hydrocarbons, C12-18**

Species		Daphnia magna (Water flea)		
EC50	>	3193		mg/l
Duration of exposure		48	h	

**hydrocarbons, C12-18**

Species		Daphnia magna (Water flea)		
NOEC	>	1000		mg/l
Duration of exposure		21	d	

**12.2. Persistence and degradability****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Biodegradability (Components)****hydrocarbons, C12-18**

Value	>	82		%
Duration of test		28	d	

**12.3. Bioaccumulative potential****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Partition coefficient: n-octanol/water**

Remarks	not determined
---------	----------------

**12.4. Mobility in soil****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Mobility in soil**

no data available

**12.5. Results of PBT and vPvB assessment****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**12.6. Other adverse effects****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**General information / ecology**

For this subsection there is no ecotoxicological data available on the product as such.

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

### 13. Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

##### modified product

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

##### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

##### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

### 14. Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

### 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### VOC

VOC (EU) 15,9 % 161 g/l

#### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

### 16. Other information

#### Hazard statements listed in Chapter 3

EUH066 Repeated exposure may cause skin dryness or cracking.  
 H304 May be fatal if swallowed and enters airways.  
 H317 May cause an allergic skin reaction.  
 H361d Suspected of damaging the unborn child.

Trade name: Proterra COLOR-SOLID-OIL NERO

Version: 6 / GB

Revision: 24.08.2020

Replaces Version: 5 / GB

Print date: 19.11.20

**CLP categories listed in Chapter 3**

Asp. Tox. 1	Aspiration hazard, Category 1
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Skin sensitization, Category 1

**Abbreviations**

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG - International Maritime Code for Dangerous Goods  
IATA - International Air Transport Association  
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS - European Inventory of Existing Commercial Chemical Substances  
CAS - Chemical Abstracts Service (division of the American Chemical Society)  
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL - Lowest Observed Adverse Effect Level  
LOEL - Lowest Observed Effect Level  
NOAEL - No Observed Adverse Effect Level  
NOEC - No Observed Effect Concentration  
NOEL - No Observed Effect Level  
OECD - Organisation for Economic Cooperation and Development  
VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.