



southgate®

Head Office:
Sterling House,
Hamlin Way,
King's Lynn,
Norfolk,
PE30 4NG,
United Kingdom

Material Safety Data Sheet (MSDS)

Products: FSS HOTMELT GLUES

Issue date: Thursday, 01 February 2018

PRODUCT IDENTIFICATION

Product codes: FSS12, FSS18, FSS43
Description: Hotmelt glue supplied in stick or slug form.
Intended use: Fast-set bonding of card and paper.
Ideal for all packaging applications.
Composition: EVA-copolymer, synthetic resin and wax.

HAZARDS IDENTIFICATION

Gases formed at high temperatures may irritate eyes and respiratory tract.
When in a molten state may cause serious burns.

FIRST AID MEASURES

General: In all cases of doubt seek medical attention.
Inhalation: In cases of exposure to gases formed at high temperatures remove affected person from area and give fresh air and rest. Seek medical advice if inconvenience persists.
Eye contact (cold glue particles): Remove contact lenses if worn. Separate eyelids and flush with copious amounts of water for at least 10 minutes. Seek medical advice.
Skin contact (burns): Rinse with copious amounts of cold water for at least 10 minutes or until medical advice/assistance is given if required.
Ingestion (cold glue particles): Do not induce vomiting. If vomiting occurs hold head low so stomach contents do not enter lungs. Seek immediate medical advice.

FIRE FIGHTING MEASURES

Extinguishing media: Foam, CO2, dry chemical, water spray

Fire will produce dense black smoke containing products of combustion that may be hazardous to health. Appropriate self-contained breathing apparatus may be required.

Hazardous combustion products: Carbon dioxide
Carbon monoxide

+44 (0) 1553 69 29 69

sales@southgate.eu.com

www.southgate.eu.com

VAT Registered No. GB 201 3214 83
Company Reg No. 05910826