# Safety Data Sheet ANCHOR Resin 1564 Hardener



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 830/2015 - United

Kingdom (UK)

1.1 Product identifier

Product name : Anchor 1564

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/

mixture

: Hardener. Woodworking industry.

1.3 Details of the supplier of the safety data sheet

**Supplier**: Redwood-UK Ltd

18 Arnside Road Waterlooville PO7 7UP

T: 02392 233340

e-mail address of person

responsible for this SDS

: sales@redwood-uk.com

1.4 Emergency telephone number

National advisory body/Poison Centre

**Telephone number**: Not available.

Supplier

**Telephone number** : 02392 233310

Hours of operation : 0730-1600 Mon-Fri

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Eye Irrit. 2, H319

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

#### SECTION 2: Hazards identification

**Hazard statements Precautionary statements** 

: H319 - Causes serious eye irritation. : P280 - Wear eye or face protection.

P264 - Wash hands thoroughly after handling.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

**Hazardous ingredients** 

Supplemental label

elements

: aluminium nitrate

: Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-

one and methenamine. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

#### Special packaging requirements

Not applicable.

#### 2.3 Other hazards

Other hazards which do not result in classification : None known.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture Chemical characterisation : Waterbased.

Product/ingredient name	Identifiers	%	Classification	Туре
ammonium chloride	REACH #: 01-2119487950-27 EC: 235-186-4 CAS: 12125-02-9 Index: 017-014-00-8	≥3 - <5	Acute Tox. 4, H302 Eye Irrit. 2, H319	[1] [2]
aluminium nitrate	REACH #: 01-2119979577-14 EC: 236-751-8 CAS: 13473-90-0	≥1 - <3	Eye Dam. 1, H318	[1] [2]
methenamine	REACH #: 01-2119474895-20 EC: 202-905-8 CAS: 100-97-0 Index: 612-101-00-2	≥0,3 - <1	Flam. Sol. 2, H228 Skin Sens. 1, H317	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation**: Move exposed person to fresh air. Get medical attention if symptoms occur. In case

of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

**Ingestion**: Wash out mouth with water. If material has been swallowed and the exposed person

is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health

effects persist or are severe.

**General**: Move the victim to a safe area as soon as possible. If unconscious, place in recovery

position and seek medical advice. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Allow the victim to rest in a well-ventilated area.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation**: Exposure to decomposition products may cause a health hazard. Serious effects

may be delayed following exposure.

**Ingestion**: Irritating to mouth, throat and stomach.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire. Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** 

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds metal oxide/oxides

## **SECTION 5: Firefighting measures**

#### 5.3 Advice for firefighters

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

## Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with liquid-binding material (sand, diatomite, universal binders etc.) or use a spill kit.

Large spill

: Approach the release from upwind. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product.

## 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: See Section 8 for information on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist.

## Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

## **SECTION 7: Handling and storage**

Store in accordance with local regulations. Store away from incompatible materials (see Section 10). Keep away from food, drink and animal feeding stuffs. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### 7.3 Specific end use(s)

Recommendations : Not available.

**Industrial sector specific** 

solutions

: Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
ammonium chloride	EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 20 mg/m³ 15 minutes. Form: Fume TWA: 10 mg/m³ 8 hours. Form: Fume
aluminium nitrate	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 2 mg/m³ 8 hours.

## procedures

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
ammonium chloride	DNEL	Long term Dermal	190 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	33,5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	9,9 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Dermal	114 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	11,4 mg/ kg bw/day	Consumers	Systemic
methenamine	DNEL	Short term Dermal	229 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	1400 mg/ m³	Workers	Systemic
	DNEL	Long term Dermal	8,8 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	31 mg/m³	Workers	Systemic

<b>ECTION 8: Exposure</b>	controls/p	ersonal prote	ction		
	DNEL	Short term Dermal	22,9 mg/ kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	140 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Dermal	1,9 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	6,7 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Oral	0,95 mg/ kg bw/day	Consumers	Systemic

#### **PNECs**

Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
ammonium chloride	PNEC	Fresh water	1,2 mg/l	-
	PNEC	Fresh water	11,2 mg/l	-
	PNEC	Sewage Treatment	16,2 mg/l	-
		Plant		
	PNEC	Soil	0,163 mg/kg dwt	-
aluminium nitrate	-	Fresh water	0,0003 mg/l	Assessment Factors
	-	Marine water	0,00003 mg/l	Assessment Factors
	-	Sewage Treatment	20 mg/l	Assessment Factors
		Plant		
	-	Fresh water sediment	0,0025 mg/kg dwt	-
	-	Marine water sediment	0,00025 mg/kg	-
			dwt	
	-	Soil	0,00032 mg/kg	-
			dwt	
methenamine	PNEC	Fresh water	3 mg/l	-
	PNEC	Marine	0,5 mg/l	-
	PNEC	Sewage Treatment	100 mg/l	-
		Plant		
		Fresh water sediment	11 mg/kg	-
	PNEC	Marine water sediment	1,84 mg/kg	-
	PNEC	Soil	0,58 mg/kg	-

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Use eye protection according to EN 166, designed to protect against liquid splashes. Recommended: chemical splash goggles.

Hand protection

: Wear suitable gloves tested to EN374. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

Recommended: Protective Index 6 / Breakthrough time >480 minutes: neoprene rubber 0.7 mm thickness or nitrile rubber 0.7 mm thickness

Other skin protection

: Wear work clothing with long sleeves. Cotton or cotton/synthetic overalls or coveralls are normally suitable.

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## **SECTION 8: Exposure controls/personal protection**

Long Term Exposure / high concentrations: Self-contained respirator (DIN EN

133) or full face mask (DIN EN 136)

Short term exposure / Low exposure : Half-face mask (DIN EN 140)

**Environmental exposure** 

controls

: Emissions from ventilation or work process equipment should be checked to ensure

they comply with the requirements of environmental protection legislation.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : Liquid.

Colour : Greyish-white. : Characteristic. Odour : Not available. **Odour threshold** 

Hq : 4,1 to 4,5 Melting point/freezing point : Not available. Initial boiling point and : Not available.

boiling range

Flash point : Closed cup: >100°C

**Evaporation rate** : Not available.

Flammability (solid, gas) : Not available. **Burning time** : Not applicable. **Burning rate** : Not applicable.

Upper/lower flammability or

explosive limits

: Not available.

Vapour pressure : Not available. Vapour density : Not available. Relative density : Not available.

**Density (liquid)** : 1,21 g/cm<sup>3</sup> [25°C] Solubility : Dispersible in water

Partition coefficient: n-octanol/ : Not available.

water

**Auto-ignition temperature** : Not available.

**Decomposition temperature** : Not available.

: Dynamic: 1800 to 5000 mPa·s [25 °C] **Viscosity** 

**Explosive properties** : Not available.

: Not available. **Oxidising properties** 

9.2 Other information

**VOC content (Without volume** : 0,0058 % (w/w) exclusion) 0,071 g/l

## **SECTION 10: Stability and reactivity**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

## **SECTION 10: Stability and reactivity**

**10.3 Conditions to avoid** : No specific data.

**10.4 Incompatible materials** : No specific data.

10.5 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Potential Adverse effects**

**Inhalation**: Exposure to decomposition products may cause a health hazard. Serious effects

may be delayed following exposure.

**Ingestion**: Irritating to mouth, throat and stomach.

**Eye contact** : Causes serious eye irritation.

Adverse symptoms may include the following:

pain or irritation watering redness

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
ammonium chloride	LD50 Oral	Rat - Male, Female	1410 mg/kg	-
	LD50 Oral	Rat - Male, Female	>2000 mg/kg	-
aluminium nitrate	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	2060 mg/kg	-
methenamine	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>20000 mg/kg	-

ammonium chloride: Harmful if swallowed.

methenamine: Based on available data, the classification criteria are not met.

#### **Acute toxicity estimates**

Product	ATE value
Oral	35427,1 mg/kg

**Product Conclusion/** 

Summary

: Based on available data, the classification criteria are not met.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ammonium chloride	Skin - Oedema	Rabbit	0	24 hours	48 hours
	Skin - Erythema/Eschar	Rabbit	0	24 hours	48 hours

**Skin**: ammonium chloride: Non-irritating to the skin.

aluminium nitrate: Slightly irritating to the skin.

methenamine: Based on available data, the classification criteria are not met.

**Eyes** : ammonium chloride: Irritating to eyes.

aluminium nitrate: Risk of serious damage to eyes.

methenamine: Based on available data, the classification criteria are not met.

Product Conclusion/

: Causes serious eye irritation.

Summary

## **SECTION 11: Toxicological information**

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
ammonium chloride methenamine	skin skin		Not sensitizing Sensitising

Skin : ammonium chloride: Not sensitizing

aluminium nitrate: Not sensitizing

methenamine: Sensitising

**Respiratory**: methenamine: Based on available data, the classification criteria are not met.

**Product Conclusion/** 

**Summary** 

: Based on available data, the classification criteria are not met.

#### **Chronic toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
methenamine	Chronic NOAEL Oral	Rat - Male	1500 to 2000 mg/	104 weeks; 7 days per week
	Chronic NOAEL Oral	Rat - Female	2000 to 2500 mg/	104 weeks; 7
	Chronic NOAEL Oral	Rat - Male	kg >80 mg/kg	days per week 50 weeks; 5
	Chronic NOAEL Oral	Rat - Female	>100 mg/kg	days per week 50 weeks; 5 days per week

#### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
ammonium chloride	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro	Positive
		Subject: Bacteria Metabolic activation: + & -	
	-	Experiment: In vitro Subject: Mammalian-Animal	Positive
	-	Experiment: In vivo Subject: Mammalian-Animal	Negative
methenamine	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Experiment: In vitro	Positive
	OECD 471 Bacterial Reverse Mutation Test	Subject: Mammalian-Animal Experiment: In vitro	Negative
		Subject: Bacteria Metabolic activation: + & -	

methenamine: Based on available data, the classification criteria are not met.

Product Conclusion/ Summary : Based on available data, the classification criteria are not met.

#### Carcinogenicity

Product Conclusion/ Summary : Based on available data, the classification criteria are not met.

## Reproductive toxicity

methenamine: Based on available data, the classification criteria are not met.

Product Conclusion/ Summary : Based on available data, the classification criteria are not met.

## **SECTION 11: Toxicological information**

#### **Teratogenicity**

**Product Conclusion/** 

**Summary** 

: Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

**Aspiration hazard** 

**Product Conclusion/** 

**Summary** 

: Based on available data, the classification criteria are not met.

Interactive effects : No specific data.

Other information : No specific data.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ammonium chloride	EC50 1618 mg/l Fresh water	Micro-organism	30
			minutes Static
	NOEC 26,8 mg/l Marine water	Algae - Navicula sp.	10 days
	= u = u,u g a a	l agent reasonal op :	Static
	Acute EC50 101 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	A	Fish Owniews same	Static
	Acute LC50 209 mg/l	Fish - Cyprinus carpio	96 hours Semi-
			static
	Chronic NOEC 14,6 mg/l Fresh water	Daphnia - Daphnia magna	21 days
			Static
	Chronic NOEC 11,8 mg/l	Fish - Pimephales promelas	28 days
			Flow through
aluminium nitrate	Acute NOEC >1000 mg/l	Fish	96 hours
methenamine	Acute EC50 3000 mg/l Fresh water	Algae - Selenastrum	14 days
		capricornutum	
	Acute EC50 >100 mg/l Fresh water	Micro-organism - Nitrosomas sp.	
	4	& Nitrobacter sp	Static
	Acute LC50 36000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	A custo I CEO 44000 mg/l Eroob water	Figh I appearing the average investigation	Static
	Acute LC50 41000 mg/l Fresh water	Fish - Lepomis macrochirus	96 hours Static
			Static

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
methenamine	-	-	Not readily

## **SECTION 12: Ecological information**

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
ammonium chloride	-3,2	-	low
methenamine	-2,18	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

**PBT**: Not applicable.

vPvB : Not applicable.

**12.6 Other adverse effects**: No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 04 99	wastes not otherwise specified

#### **Packaging**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

#### SECTION 14: Transport information ADR/RID **ADN IMDG** IATA 14.1 UN number Not regulated. Not regulated. Not regulated. Not regulated. 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 No. No. No. No. **Environmental** hazards Additional

14.6 Special precautions for user

information

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

#### Other EU regulations

**Europe inventory** : All components are listed or exempted.

**Black List Chemicals** : Not listed **Priority List Chemicals** : Not listed Integrated pollution : Not listed

(IPPC) - Air

Integrated pollution prevention and control list

prevention and control list

(IPPC) - Water

: Not listed

**Seveso II Directive** 

## **SECTION 15: Regulatory information**

This product is not controlled under the Seveso II Directive.

#### **National regulations**

#### Chemical Weapon Convention List Schedules I. II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A. B. C. E)

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical Safety

**Assessment** 

: This product contains substances for which Chemical Safety Assessments are still

required.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and** 

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification		Justification	
Eye Irrit. 2, H319		Calculation method	
Full text of abbreviated H statements	: H228 H302 H317 H318 H319	Flammable solid. Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation.	
Full text of classifications [CLP/GHS]	Eye Irrit. 2, H319 Flam. Sol. 2, H228 Skin Sens. 1, H317	ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE SOLIDS - Category 2 SKIN SENSITIZATION - Category 1	

Date of issue/ Date of

revision

: 12/05/2022

Date of previous issue

: n/a

**Previous product name** 

: Not available.

Version

: 1