



### >General information

|                         |                 |
|-------------------------|-----------------|
| Colour                  | braun           |
| Colour card designation | Hesse Beiz-Töne |
| Colour tone             | BE 15-20402     |
| Colour designation      | BE 15-20402     |
| Form of delivery        | fluid           |
| Product type            | Stain           |
| Order number            | CL 15-7331      |
| Effects                 | Stained         |
| Chemistry               | Solvent stains  |
| Colourfulness           | coloured        |
| Function                | Lackbeizen      |

### >Areas of application

|                     |   |
|---------------------|---|
| Substrate material  | dark deciduous woods with coarse pores  |
| Area of application | Counter tops, Hotels, Kitchen bathroom, Shopfitting, Door frames, Tables, Residential |

### >Mixing information

|                   |                |
|-------------------|----------------|
| Thinners          | CV 326, CV 326 |
| Retarder          | CV 555         |
| Equipment cleaner | RV 1           |

### >Application

|                            |  |
|----------------------------|--|
| Treatment                  | Airless low pressure, Airmix, Compressed air spraying, Wiping with a cloth |
| Number of coats (max)      | 1  |
| Amount per layer (minimum) | 50 g/m <sup>2</sup>  |
| Amount per layer (max)     | 80 g/m <sup>2</sup>  |
| Total application volume   | 80 g/m <sup>2</sup>  |

### >Times

|        |             |
|--------|-------------|
| Drying | 1 h / 20 °C |
|--------|-------------|

### >Technical data

|                                       |             |
|---------------------------------------|-------------|
| Proportion of renewable raw materials | 11.179 %    |
| Flow time (+/- 15%)                   | 60 s / ISO3 |
| Appearance                            | glazing     |
| Density                               | 0.92 kg/l   |
| Flashpoint (min)                      | 21 °C       |
| Non-volatile proportion               | 3.9 %       |
| VOC EU                                | 95.6 %      |
| VOC FR                                | C           |

### >Others

|                         |                               |
|-------------------------|-------------------------------|
| Shelf life in weeks     | 52                            |
| conditions of transport | frost-free - up to max. 35 °C |

#### Particular instructions:

Lighten by adding: CV 326. Can be tinted with colour concentrates in the range: CF 50xx, CP 70xx, CP 76xx. Stains on the XBK 6 stain card are adjusted for oak and mahogany. Hesse stains are matched to each type of wood in terms of colour tone and application. Additional types of application and woods are available.